Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	39123183
Valid rim size	DW 23 B x 42
Rim connection	10/281/335
Offset (mm)	-55
Brand	Levypyoera

Technical Informations

Load capacity of rim 1 [kg]	8320
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	206,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	coated
Rim colour (manufacturer's designation)	Fendt Terra - red
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Dise this lunces [mm]	10
Disc thickness [mm]	18
Verschweißung beidseitig	No
Number of additional holes	6
Additional pitch circle diameter [mm].	865
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	10
Bolt hole diameter [mm]	24
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.