

RIMS

Product group	Rims
Item number	39160055
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+133
Half centre distance (HMA) [mm]	145
Rim colour	Silver
Brand	Jantasa



Technical Informations

Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	100
Load capacity of rim 3 [kg]	6300
Speed Rims 3 [km/h]	5
Maximum speed [km/h].	100
Nettogewicht [kg] (gültig)	24,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel

RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No