Bohnenkamp Moving Professionals

19.09.2024

RIMS

Product group	Rims
Item number	39600064
Valid rim size	5.50 A x 8 H
Rim connection	4/61/100
Rim colour	Silver
Brand	Vlukon





Technical Informations

Load capacity of rim 1 [kg]	350
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	2,65
Hump	н
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	15
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	61
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No