Bohnenkamp Moving Professionals

20.09.2024

RIMS

Product group	Rims
Item number	39600154
Valid rim size	4.00 B x 12 H2
Rim connection	4/60/100
Rim colour	Silver
Brand	Vlukon





Technical Informations Load capacity of rim 1 [kg] 475 Speed Rims 1 [km/h] 100 Maximum speed [km/h]. 100 Type of drive Towed axle Nettogewicht [kg] (gültig) 4,60 Hump H2 Single / multi-part einteilig **Rim material** steel RAL RAL9006 **Cavity Sealed** No Verschweißung beidseitig No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	13.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	12.5
Preassembled valve	No