Bohnenkamp Moving Professionals

05.02.2025

RIMS

Product group	Rims
Item number	39600300
Valid rim size	3.50 x 6 H2
Rim connection	4/60/90
Rim colour	Silver
Brand	Vlukon





Technical Informations Load capacity of rim 1 [kg] 325 Speed Rims 1 [km/h] 16 Load capacity of rim 2 [kg] 145 Speed Rims 2 [km/h] 30 Load capacity of rim 3 [kg] 250 Speed Rims 3 [km/h] 20 Maximum speed [km/h]. 30 Type of drive Towed axle Nettogewicht [kg] (gültig) 1,30 Hump H2 Single / multi-part einteilig

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	1.75
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	8.5
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	90
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No

05.02.2025