Bohnenkamp Moving Professionals

19.09.2024

RIMS

Product group	Rims
Item number	39600320
Valid rim size	2.10 - 4
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	75
Hub length [mm]	75
Rim colour	Silver
Brand	Knochenmuß





Technical Informations

Load capacity of rim 1 [kg]	400
Speed Rims 1 [km/h]	16
Maximum speed [km/h].	16
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	0,70
Hump	kein Hump
Single / multi-part	geteilt
Rim material	steel
RAL	RAL9006
Verschweißung beidseitig	No
Offset hub	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	11.0
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.