

RIMS

Product group	Rims
Item number	39600371
Valid rim size	13 LB x 15 H2
Rim connection	5/192/225
Bolt hole design	A1
Offset (mm)	+83.5
Rim colour	Grey
Brand	Starco

Technical Informations

Load capacity of rim 1 [kg]	1900
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	1730
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	19,90
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL7042

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	192
Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No