

RIMS

| | |
|------------------|-------------|
| Product group | Rims |
| Item number | 39600666 |
| Valid rim size | 6 J x 13 H2 |
| Rim connection | 5/67/112 |
| Bolt hole design | E12 |
| Offset (mm) | +30 |
| Rim colour | Silver |
| Brand | Kenda |



Technical Informations

| | |
|-----------------------------|------------|
| Load capacity of rim 1 [kg] | 950 |
| Speed Rims 1 [km/h] | 140 |
| Maximum speed [km/h]. | 140 |
| Type of drive | Towed axle |
| Nettogewicht [kg] (gültig) | 9,00 |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Disc thickness [mm] | 5 |

| | |
|--------------------------------|----------------|
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole diameter [mm] | 16 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R12 |
| hub hole diameter [mm]. | 67 |
| Bolt hole circle diameter [mm] | 112 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |
| Preassembled valve | No |