Bohnenkamp Moving Professionals

05.02.2025

RIMS

Product group	Rims
Item number	39600672
Valid rim size	5.5 J x 14 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+30
Rim colour	Silver
Brand	Kenda





Load capacity of rim 1 [kg] 950 Speed Rims 1 [km/h] 140 Maximum speed [km/h]. 140 Type of drive Towed axle Nettogewicht [kg] (gültig) 9,40 Hump H2 Single / multi-part einteilig **Rim material** steel RAL RAL9006 Colour type Glossy **Cavity Sealed** No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Technical Informations

Bohnenkamp Moving Professionals

Disc thickness [mm]	5
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No