## Bohnenkamp Moving Professionals

## RIMS

Product group	Rims
Item number	39600766
Valid rim size	9.00 I x 12 H2
Rim connection	6/90/120
Offset (mm)	-33
Brand	Starco

## **Technical Informations**

Load capacity of rim 1 [kg]	1030
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Nettogewicht [kg] (gültig)	8,80
Hump	H2
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Kubota - orange
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

Rim centering	НВ
Number of bolt holes	6
Bolt hole diameter [mm]	14
hub hole diameter [mm].	90
Bolt hole circle diameter [mm]	120
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.