## Bohnenkamp Moving Professionals

## RIMS

Product group	Rims
Item number	39800100
Valid rim size	6.5 J x 16 H2
Rim connection	5/110/145
Offset (mm)	-10
Rim colour	Silver
Brand	Brock



## **Technical Informations**

Load capacity of rim 1 [kg]	1350
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	11,50
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	15
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	110
Bolt hole circle diameter [mm]	145
Valve seat	External Valve
Valve hole diameter [mm]	12.5
Preassembled valve	No