Bohnenkamp Moving Professionals

19.09.2024

RIMS

Product group	Rims
Item number	39920102
Valid rim size	3.00 D - 8
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	100
Hub length [mm]	100
Rim colour	Silver
Brand	Vlukon





Technical Informations	
Load capacity of rim 1 [kg]	820
Speed Rims 1 [km/h]	16
Maximum speed [km/h].	16
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	3,75
Hump	kein Hump
Single / multi-part	geteilt
Rim material	steel
RAL	RAL9006
Rim design industry	Standard
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	13.0
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.