

RIMS

Product group	Rims
Item number	39920534
Valid rim size	7.50 x 22.5
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-138
Rim colour	Black
Brand	Jantsa





Technical Informations		
Load capacity of rim 1 [kg]	4800	
Speed Rims 1 [km/h]	25	
Load capacity of rim 2 [kg]	2300	
Speed Rims 2 [km/h]	65	
Maximum speed [km/h].	65	
Type of drive	Towed axle	
Nettogewicht [kg] (gültig)	25,00	
Hump	kein Hump	
Valve protection	VS H	
Single / multi-part	einteilig	
Rim material	steel	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9005
Cavity Sealed	No
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Preassembled valve	No