

AUTOMOTIVE COMPONENTS

Product group	Automotive components
Item number	40476023
Track width [mm]	2050
Square axle beam [mm]	150
Number of bolt holes	10
Hub diameter [mm].	280.5
Pitch circle diameter [mm]	335
Brake size	420X180





Technical Informations

Brand	ADR
Axle load 40 km/h (single axle) [kg].	15700
Axle load 40 km/h (tandem) [kg]	14500
Axle load 40 km/h (two-axle vehicles) [kg]	15700
Axle load 60 km/h (single axle) [kg].	14100
Axle load 60 km/h (tandem) [kg]	13100
Axle load 60 km/h (two-axle vehicles) [kg].	14100
Axle load > 60 km/h (single axle) [kg].	12900
Axle load > 60 km/h (tandem) [kg]	11900
Axle load > 60 km/h (two-axle vehicles) [kg]	12900
Type of brake	Pneumatic operated

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Brake size	420X180
Brake type	4218E
ABS	No
Version of brake lever	Slack adjuster
Distance between brake lever [mm].	722
Brake lever lengths [mm]	203,178,152,127
Wheel stud design	Single
Wheel stud type	M22
Thread	M22 x 1,5
Bearing pairing	4V
Base plate diaphragm cylinder	Welded
Surface treatment	primed
Colour	Black
Colour type	Matt
RAL	RAL9005
Axle beam design	Hollow body
Axle plates welded on	No
Nettogewicht [kg] (gültig)	380,00