

WHEELS

Product group	Wheels
Item number	52727705
Valid wheel size	300 / 95 R 52
Brand	BKT
Tread pattern	Agrimax RT 955
Valid rim size	W 10 x 52
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+100
Rim colour	Silver
Load capacity complete wheel [kg]	3450
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15727700
LI / SI / PR	151 A8 / 151 B
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Load capacity 2 [kg]	3450
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	307,75
ECE regulation number	ECE 106
Section width (mm)	295

Stat. radius (SLR) [mm]	889
Rolling circumference [mm].	5774
Tread depth (mm)	36,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	224
E-Ready	No
Assembly Item no. Rim	• 39122997
Load capacity of rim 1 [kg]	3960
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade