

WHEELS

Product group	Wheels
Item number	58692080
Valid wheel size	16.5 x 6.50 - 8
Brand	Cheng Shin
Tread pattern	C834
Valid rim size	5.50 A x 8
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	350
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 10714870
LI / SI / PR	77 M, 8 PR
Load capacity 1 [kg]	412
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	7,02
ECE regulation number	ECE 54
Section width (mm)	168
E-Ready	No
Assembly Item no. Rim	• 30655030

Load capacity of rim 1 [kg]	575
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	350
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	6,20
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0

Valve angle [°]

gerade
