

WHEELS

Product group	Wheels
Item number	58692091
Valid wheel size	18.5 x 8.50 - 8
Brand	Trailermaxx
Tread pattern	C834
Valid rim size	7.00 A x 8 H2
Rim connection	5/79.5/114.3
Rim colour	Silver
Load capacity complete wheel [kg]	515
Speed complete wheel [km/h]	10
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 10714892
LI / SI / PR	85 M, 8 PR
Load capacity 1 [kg]	515
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	8,93
ECE regulation number	ECE 54
Section width (mm)	210
E-Ready	No
Assembly Item no. Rim	• 30895257

Load capacity of rim 1 [kg]	535
Speed Rims 1 [km/h]	10
Maximum speed [km/h].	10
Maximum air pressure [bar].	4,80
Number of bolt holes	5
hub hole diameter [mm].	79.5
Bolt hole circle diameter [mm]	114.3
Bolt hole diameter [mm]	12.5
Countersinking	Cone
Countersinking of the cone [°].	C60
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade