

WHEELS

Product group	Wheels
Item number	58692092
Valid wheel size	18.5 x 8.50 - 8
Brand	Trailermaxx
Tread pattern	C834
Valid rim size	7.00 A x 8 H2
Rim connection	5/79.5/114.3



Technical Informations

Assembly Item no. Tyres	• 10714892
LI / SI / PR	85 M, 8 PR
Load capacity 1 [kg]	515
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	8,93
ECE regulation number	ECE 54
Section width (mm)	210
E-Ready	No
Assembly Item no. Rim	• 30895258

Load capacity of rim 1 [kg]	525
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,80
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	John Deere - yellow
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	12.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	79.5
Bolt hole circle diameter [mm]	114.3
Valve seat	External Valve
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade