

WHEELS

Product group	Wheels
Item number	58692120
Valid wheel size	6.00 - 9
Brand	ВКТ
Tread pattern	PL 801
LI / SI / PR	114 A8, 10 PR
TL/TT	тт
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	35
Mounting length [mm]	120
Hub length [mm]	120
Rim colour	Silver



Technical Informations

Assembly Item no. Tyres •	15771070
Alternative size 1	6.90-9
LI / SI / PR	114 A8, 10 PR
TL/TT	тт
Brand	BKT
Tread pattern	PL 801
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Maximum air pressure [bar].	8,50

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Section width (mm)	157
Tread depth (mm)	14,0
Assembly Item no. Rim •	30695310
Valid rim size	4.00 E - 9
Load capacity of rim 1 [kg]	1010
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	25
Hump	kein Hump
Single / multi-part	geteilt
Quantity multi-piece	two-part
Rim material	steel
RAL	RAL9006
Grease nipple	Grease nipples
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Valve designation	JS 2