

WHEELS

Product group	Wheels
Item number	59600032
Valid wheel size	155 R 12 C
Brand	Maxxis
Tread pattern	UE-168
Valid rim size	4.5 J x 12 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	20
Rim colour	Silver
Load capacity complete wheel [kg]	560
Speed complete wheel [km/h]	140
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 10765028
LI / SI / PR	88 / 86 N, 8 PR
Load capacity 1 [kg]	560
Speed 1 [km/h].	140
Load capacity 3 [kg]	530
Speed 3 [km/h].	140
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	14,42

ECE regulation number	ECE 54
Section width (mm)	156
Rolling resistance	D
Wet grip	B
Rolling noise [db].	70
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600636
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,33
Number of bolt holes	5
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	5
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade