

WHEELS

Product group	Wheels
Item number	59600046
Valid wheel size	155 R 13 C
Brand	Security
Tread pattern	TR603
Valid rim size	4.5 J x 13 H2
Rim connection	4/57/100
Bolt hole design	E16
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	600
Speed complete wheel [km/h]	140



Bohnenkamp
■ ■ ● Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 18345277
LI / SI / PR	91 / 89 N (90 / 88 R), 8 PR
Load capacity 1 [kg]	615
Speed 1 [km/h].	140
Load capacity 2 [kg]	600
Speed 2 [km/h].	170
Load capacity 3 [kg]	580
Speed 3 [km/h].	140
Load capacity 4 [kg]	560
Speed 4 [km/h].	170
M+S	M+S

Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	11,92
ECE regulation number	ECE 54 ECE 117
Section width (mm)	157
Stat. radius (SLR) [mm]	270
Rolling circumference [mm].	1751
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600309
Load capacity of rim 1 [kg]	600
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC

Number of bolt holes	4
Bolt hole diameter [mm]	15.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade