

WHEELS

Product group	Wheels
Item number	59600050
Valid wheel size	155 R 13
Brand	Trailermaxx
Tread pattern	CR-966
Valid rim size	4.5 J x 13 H2
Rim connection	4/57/100
Bolt hole design	E16
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	600
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 10745052
LI / SI / PR	91 / 89 N
Load capacity 1 [kg]	615
Speed 1 [km/h].	140
Load capacity 3 [kg]	580
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	12,22
ECE regulation number	ECE 54 ECE 117

Section width (mm)	158
Rolling resistance	C
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600309
Load capacity of rim 1 [kg]	600
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	2,70
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	15.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	100

Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade