

## WHEELS

|                                   |               |
|-----------------------------------|---------------|
| Product group                     | Wheels        |
| Item number                       | 59600052      |
| Valid wheel size                  | 155 R 13      |
| Brand                             | Trailermaxx   |
| Tread pattern                     | CR-966        |
| Valid rim size                    | 4.5 J x 13 H2 |
| Rim connection                    | 5/67/112      |
| Bolt hole design                  | E12           |
| Offset (mm)                       | +30           |
| Rim colour                        | Silver        |
| Load capacity complete wheel [kg] | 615           |
| Speed complete wheel [km/h]       | 140           |



## Technical Informations

|                            |                |
|----------------------------|----------------|
| Assembly Item no. Tyres    | • 10745052     |
| LI / SI / PR               | 91 / 89 N      |
| Load capacity 1 [kg]       | 615            |
| Speed 1 [km/h].            | 140            |
| Load capacity 3 [kg]       | 580            |
| Speed 3 [km/h].            | 140            |
| M+S                        | M+S            |
| Antistatic                 | No             |
| Tyre colour                | Black          |
| Nettogewicht [kg] (gültig) | 12,12          |
| ECE regulation number      | ECE 54 ECE 117 |

|                                |            |
|--------------------------------|------------|
| Section width (mm)             | 158        |
| Rolling resistance             | C          |
| Wet grip                       | B          |
| Rolling noise [db].            | 72         |
| Rolling noise level            | B          |
| E-Ready                        | No         |
| Assembly Item no. Rim          | • 30045101 |
| Load capacity of rim 1 [kg]    | 625        |
| Speed Rims 1 [km/h]            | 140        |
| Maximum speed [km/h].          | 140        |
| Maximum air pressure [bar].    | 2,70       |
| Type of drive                  | Towed axle |
| Hump                           | H2         |
| Single / multi-part            | einteilig  |
| Rim material                   | steel      |
| RAL                            | RAL9006    |
| Cavity Sealed                  | No         |
| Disc thickness [mm]            | 4.25       |
| Ventilation holes              | Yes        |
| Verschweißung beidseitig       | No         |
| Rim centering                  | BC         |
| Number of bolt holes           | 5          |
| Bolt hole diameter [mm]        | 16         |
| Countersinking                 | Sphere     |
| Spherical countersink [mm].    | R12        |
| hub hole diameter [mm].        | 67         |
| Bolt hole circle diameter [mm] | 112        |

---

|                          |                |
|--------------------------|----------------|
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 11.3           |
| Preassembled valve       | No             |
| Valve design             | Rubber valve   |
| Valve designation ETRTO  | V2.03.1        |
| Valve length [mm]        | 43.0           |
| Valve angle [°]          | gerade         |