

## WHEELS

Product group	Wheels
Item number	59600113
Valid wheel size	165 R 13 C
Brand	Security
Tread pattern	TR603
Valid rim size	5 J x 13 H2
Rim connection	4/57/100
Bolt hole design	E16
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	700
Speed complete wheel [km/h]	140



Bohnenkamp  
■ ■ ● Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 18366151
LI / SI / PR	96 N (94 / 92 R)
Load capacity 1 [kg]	710
Speed 1 [km/h].	140
Load capacity 2 [kg]	670
Speed 2 [km/h].	170
Load capacity 4 [kg]	630
Speed 4 [km/h].	170
M+S	M+S
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	16,27
ECE regulation number	ECE 54 ECE 117
Section width (mm)	165
Stat. radius (SLR) [mm]	278
Rolling circumference [mm].	1806
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30055087
Load capacity of rim 1 [kg]	700
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	15.5
Countersinking	Cone

---

Countersinking of the cone [°].	C60
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade