

## WHEELS

Product group	Wheels
Item number	59600119
Valid wheel size	175 R 14 C
Brand	Nankang
Tread pattern	CW-25
Valid rim size	5 J x 14
Rim connection	5/67/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	930
Speed complete wheel [km/h]	40



Bohnenkamp  
Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 19965225
LI / SI / PR	99 / 98 R
Load capacity 1 [kg]	775
Speed 1 [km/h].	170
Load capacity 3 [kg]	750
Speed 3 [km/h].	170
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	17,61
ECE regulation number	ECE 54 ECE 117
Section width (mm)	178

Rolling resistance	C
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30820120
Load capacity of rim 1 [kg]	1020
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	930
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,50
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112

---

Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade