Bohnenkamp Moving Professionals

20.09.2024

WHEELS

Product group	Wheels
Item number	59600133
Valid wheel size	185 / 70 R 13
Brand	BK Trailer
Tread pattern	202
Valid rim size	4.5 J x 13 H2
Rim connection	4/57/100
Bolt hole design	E16
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	600
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	18545060
LI / SI / PR	93 N
Load capacity 1 [kg]	650
Speed 1 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	13,12
ECE regulation number	ECE 30 ECE 117
Section width (mm)	197
Stat. radius (SLR) [mm]	266

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

20.09.2024

Rolling circumference [mm].	1800
Tread depth (mm)	5,5
Rolling resistance	D
Wet grip	D
Rolling noise [db].	71
Rolling noise level	В
E-Ready	No
Assembly Item no. Rim	39600309
Load capacity of rim 1 [kg]	600
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	3,00
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	15.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	57

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.