

## WHEELS

Product group	Wheels
Item number	59600162
Valid wheel size	175 R 14 C
Brand	Nankang
Tread pattern	CW-25
Valid rim size	5.5 J x 14 H2
Rim connection	4/57/100
Bolt hole design	E16
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	140
Nettogewicht [kg] (gültig)	18,92
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp  
Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 19965225
LI / SI / PR	99 / 98 R
Load capacity 1 [kg]	775
Speed 1 [km/h].	170
Load capacity 3 [kg]	750
Speed 3 [km/h].	170
Maximum air pressure [bar].	4,50
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 54 ECE 117
Rolling resistance	C
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Section width (mm)	178
Assembly Item no. Rim	• 39600671
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Type of drive	Towed axle
Number of bolt holes	4
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	100
Bolt hole diameter [mm]	15.5
Countersinking	Cone
Countersinking of the cone [°].	C60
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2

---

Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200650
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade