

## WHEELS

Product group	Wheels
Item number	59600340
Valid wheel size	185 R 14 C
Brand	Security
Tread pattern	TR603
Valid rim size	5.5 J x 14 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



Bohnenkamp  
■ ■ ● Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 18366207
LI / SI / PR	102 / 100 S (104 N), 8 PR
Load capacity 1 [kg]	850
Speed 1 [km/h].	180
Load capacity 2 [kg]	900
Speed 2 [km/h].	140
Load capacity 3 [kg]	800
Speed 3 [km/h].	180
M+S	M+S
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	18,52
ECE regulation number	ECE 54 ECE 117
Section width (mm)	188
Stat. radius (SLR) [mm]	303
Rolling circumference [mm].	1970
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600672
Load capacity of rim 1 [kg]	950
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Disc thickness [mm]	5
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5

---

<b>Bolt hole diameter [mm]</b>	16
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R12
<b>hub hole diameter [mm].</b>	67
<b>Bolt hole circle diameter [mm]</b>	112
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	11.3
<b>Preassembled valve</b>	No
<b>Valve design</b>	Rubber valve
<b>Valve designation ETRTO</b>	V2.03.1
<b>Valve length [mm]</b>	43.0
<b>Valve angle [°]</b>	gerade