

WHEELS

Product group	Wheels
Item number	59600349
Valid wheel size	185 R 14 C
Brand	Security
Tread pattern	TR603
Valid rim size	6 J x 14 H2
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



Bohnenkamp
Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 18366207
LI / SI / PR	102 / 100 S (104 N), 8 PR
Load capacity 1 [kg]	850
Speed 1 [km/h].	180
Load capacity 2 [kg]	900
Speed 2 [km/h].	140
Load capacity 3 [kg]	800
Speed 3 [km/h].	180
M+S	M+S
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	19,42
ECE regulation number	ECE 54 ECE 117
Section width (mm)	188
Stat. radius (SLR) [mm]	303
Rolling circumference [mm].	1970
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39800450
Load capacity of rim 1 [kg]	1250
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere

Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade