

WHEELS

Product group	Wheels
Item number	59600518
Valid wheel size	195 R 14 C
Brand	BK Trailer
Tread pattern	203
Valid rim size	5.5 J x 14 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	950
Speed complete wheel [km/h]	140
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 18545110
LI / SI / PR	108 / 106 N
Load capacity 1 [kg]	1000
Speed 1 [km/h].	140
Load capacity 3 [kg]	950
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	19,31
ECE regulation number	ECE 54 ECE 117
Section width (mm)	198
Stat. radius (SLR) [mm]	302
Rolling circumference [mm].	2018
Tread depth (mm)	6,0
Rolling resistance	D
Wet grip	D
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600672
Load capacity of rim 1 [kg]	950
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	5,00
Number of bolt holes	5
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel

RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Disc thickness [mm]	5
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	45.5
Valve angle [°]	gerade