

WHEELS

Product group	Wheels
Item number	59600521
Valid wheel size	195 R 14 C
Brand	BK Trailer
Tread pattern	203
Valid rim size	5.5 J x 14 H2
Rim connection	5/66.6/112
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	950
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	18545110
LI / SI / PR	108 / 106 N
Load capacity 1 [kg]	1000
Speed 1 [km/h].	140
Load capacity 3 [kg]	950
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	17,33
ECE regulation number	ECE 54 ECE 117

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Section width (mm)	198
Stat. radius (SLR) [mm]	302
Rolling circumference [mm].	2018
Tread depth (mm)	6,0
Rolling resistance	D
Wet grip	D
Rolling noise [db].	72
Rolling noise level	В
E-Ready	No
Assembly Item no. Rim	39800430
Load capacity of rim 1 [kg]	950
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	5,00
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	15
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	66.6

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.4
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade