

## WHEELS

Product group	Wheels
Item number	59600616
Valid wheel size	195 / 75 R 16 C
Brand	Mirage
Tread pattern	MR-W300
Valid rim size	6 J x 16 H2
Rim connection	5/94/140
Bolt hole design	E1
Offset (mm)	+68
Rim colour	Silver
Load capacity complete wheel [kg]	975
Speed complete wheel [km/h]	50



Bohnenkamp  
■ ■ ● Moving Professionals

**MIRAGE**

## Technical Informations

Assembly Item no. Tyres	• 10165840
LI / SI / PR	107 / 105 R, 8 PR
Load capacity 1 [kg]	975
Speed 1 [km/h].	170
Load capacity 3 [kg]	925
Speed 3 [km/h].	170
M+S	M+S
3PMSF	3PMSF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	27,83

ECE regulation number	ECE 117 ECE 54
Section width (mm)	196
Tread width (mm)	195
Stat. radius (SLR) [mm]	320
Rolling circumference [mm].	2115
Tread depth (mm)	8,7
Rolling resistance	D
Wet grip	D
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30855362
Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	50
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,75
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere

---

Spherical countersink [mm].	R14
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade