

WHEELS

Product group	Wheels
Item number	59600645
Valid wheel size	225 / 75 R 16 C
Brand	Onyx
Tread pattern	NY-AS 687
Valid rim size	6 J x 16 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	1450
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 10165260
LI / SI / PR	121 / 120 R, 12 PR
Load capacity 1 [kg]	1450
Speed 1 [km/h].	170
Load capacity 3 [kg]	1400
Speed 3 [km/h].	170
M+S	M+S
3PMSF	3PMSF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	28,73

ECE regulation number	ECE 54 ECE 117
Section width (mm)	223
Tread depth (mm)	9,7
Rolling resistance	D
Wet grip	D
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30855340
Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	5,75
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade