

WHEELS

Product group	Wheels
Item number	59600708
Valid wheel size	205 R 14 C
Brand	BK Trailer
Tread pattern	203
Valid rim size	5.5 J x 14 H2
Rim connection	5/66.6/112
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	950
Speed complete wheel [km/h]	140



Bohnenkamp
Moving Professionals

Technical Informations

Assembly Item no. Tyres	• 18545120
LI / SI / PR	109 / 107 N
Load capacity 1 [kg]	1030
Speed 1 [km/h].	140
Load capacity 3 [kg]	975
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	18,33
ECE regulation number	ECE 54 ECE 117

Section width (mm)	208
Stat. radius (SLR) [mm]	310
Rolling circumference [mm].	2079
Tread depth (mm)	6,0
Rolling resistance	D
Wet grip	D
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39800430
Load capacity of rim 1 [kg]	950
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,48
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	15
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	66.6

Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.4
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade