

WHEELS

Product group	Wheels
Item number	59600927
Valid wheel size	215 R 14 C
Brand	BK Trailer
Tread pattern	203
Valid rim size	5.5 J x 14 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	950
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 18545130
LI / SI / PR	116 / 114 N
Load capacity 1 [kg]	1250
Speed 1 [km/h].	140
Load capacity 3 [kg]	1180
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	20,73
ECE regulation number	ECE 54 ECE 117

Section width (mm)	218
Stat. radius (SLR) [mm]	315
Rolling circumference [mm].	2121
Tread depth (mm)	6,0
Rolling resistance	D
Wet grip	D
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600672
Load capacity of rim 1 [kg]	950
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,75
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Disc thickness [mm]	5
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16

Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade