

## WHEELS

Product group	Wheels
Item number	59600969
Valid wheel size	225 / 70 R 15 C
Brand	Kenda
Tread pattern	KR101 MasterTrail 3G
Valid rim size	6 J x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	140



Bohnenkamp  
■ ■ ● Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 19266146
LI / SI / PR	116 / 114 N
Load capacity 1 [kg]	1250
Speed 1 [km/h].	140
Load capacity 3 [kg]	1180
Speed 3 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	23,92
ECE regulation number	ECE 54 ECE 117

Section width (mm)	228
Stat. radius (SLR) [mm]	314
Rolling circumference [mm].	2112
Tread depth (mm)	5,8
Rolling resistance	A
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 31610095
Load capacity of rim 1 [kg]	1285
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,75
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16

---

hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade