

WHEELS

Product group	Wheels
Item number	59600979
Valid wheel size	225 / 70 R 15 C
Brand	Onyx
Tread pattern	NY-W287
Valid rim size	6 J x 15 H2
Rim connection	5/67/112
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	900
Speed complete wheel [km/h]	140



Bohnenkamp
■ ■ ● Moving Professionals



Technical Informations

Assembly Item no. Tyres	• 10165110
LI / SI / PR	112 / 110 R, 8 PR
Load capacity 1 [kg]	1120
Speed 1 [km/h].	170
Load capacity 3 [kg]	1060
Speed 3 [km/h].	170
M+S	M+S
3PMSF	3PMSF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	20,60

ECE regulation number	ECE 54 ECE 117
Section width (mm)	228
Rolling circumference [mm].	2112
Tread depth (mm)	9,7
Rolling resistance	D
Wet grip	D
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39800440
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	15
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	67

Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.4
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade