

## WHEELS

Product group	Wheels
Item number	59638027
Valid wheel size	185 / 65 R 14
Brand	Boka Trailer Line
Tread pattern	FT 01
Valid rim size	5.5 J x 14 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	650
Speed complete wheel [km/h]	140



**BOKA TRAILER**

## Technical Informations

Assembly Item no. Tyres	• 18545370
LI / SI / PR	93 N
Load capacity 1 [kg]	650
Speed 1 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	16,52
ECE regulation number	ECE 30 ECE 117
Section width (mm)	189
Rolling circumference [mm].	1869

Tread depth (mm)	6,0
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600672
Load capacity of rim 1 [kg]	950
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	3,40
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Disc thickness [mm]	5
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67

---

<b>Bolt hole circle diameter [mm]</b>	112
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	11.3
<b>Preassembled valve</b>	No
<b>Valve design</b>	Rubber valve
<b>Valve designation ETRTO</b>	V2.03.1
<b>Valve length [mm]</b>	43.0
<b>Valve angle [°]</b>	gerade