

## WHEELS

Product group	Wheels
Item number	59696004
Valid wheel size	4.80 / 4.00 - 8
Brand	Kenda
Tread pattern	K371
Valid rim size	2.50 A x 8
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	335
Speed complete wheel [km/h]	130



Bohnenkamp  
■ ■ ● Moving Professionals

## Technical Informations

Assembly Item no. Tyres	• 19266050
LI / SI / PR	70 M, 6 PR
Load capacity 1 [kg]	335
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	3,90
ECE regulation number	ECE 54
Section width (mm)	119
Stat. radius (SLR) [mm]	176
Rolling circumference [mm].	1215

E-Ready	No
Assembly Item no. Rim	• 30655010
Load capacity of rim 1 [kg]	425
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Maximum air pressure [bar].	5,90
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve designation	TR 13