## Bohnenkamp Moving Professionals

09.11.2024

## WHEELS

Product group	Wheels
Item number	59696008
Valid wheel size	5.70 / 5.00 - 8
Brand	Deli
Tread pattern	S-378
Valid rim size	3.00 D x 8
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	300
Speed complete wheel [km/h]	100



## **Technical Informations**

Assembly Item no. Tyres	19166110
LI / SI / PR	77 M, 6 PR
Load capacity 1 [kg]	412
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	5,75
ECE regulation number	ECE 30
Section width (mm)	140
Stat. radius (SLR) [mm]	218
Rolling circumference [mm].	1425

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

09.11.2024

Tread depth (mm)	5,4
E-Ready	No
Assembly Item no. Rim	30655020
Load capacity of rim 1 [kg]	300
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	5,30
Number of bolt holes	4
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Valve length [mm]	38
Valve angle [°]	gerade
Colour of cap	Black
Valve cap Material	Plastic

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.