

## WHEELS

Product group	Wheels
Item number	59696009
Valid wheel size	16.5 x 6.50 - 8
Brand	Deli
Tread pattern	S-368
Valid rim size	5.50 A x 8
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	350



## Technical Informations

Assembly Item no. Tyres	• 19166120
LI / SI / PR	73 M, 6 PR
Load capacity 1 [kg]	365
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	6,16
ECE regulation number	ECE 30
Section width (mm)	166
Stat. radius (SLR) [mm]	190
Rolling circumference [mm].	1284

Tread depth (mm)	5,2
E-Ready	No
Assembly Item no. Rim	• 30655030
Load capacity of rim 1 [kg]	575
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	350
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	4,80
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No

---

Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade