

WHEELS

Product group	Wheels
Item number	59696010
Valid wheel size	18.5 x 8.50 - 8
Brand	Kenda
Tread pattern	K368
Valid rim size	7.00 A x 8 H2
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	425
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 19266056
LI / SI / PR	78 M, 6 PR
Load capacity 1 [kg]	425
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	9,30
ECE regulation number	ECE 54
Section width (mm)	220
E-Ready	No
Assembly Item no. Rim	• 30695185

Load capacity of rim 1 [kg]	425
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	3,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.5
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade