

## WHEELS

Product group	Wheels
Item number	59696012
Valid wheel size	5.00 - 10
Brand	Kenda
Tread pattern	K364
Valid rim size	3.50 B x 10 H2
Rim connection	4/60/100
Rim colour	Silver
Load capacity complete wheel [kg]	437
Speed complete wheel [km/h]	130



## Technical Informations

Assembly Item no. Tyres	• 19266061
LI / SI / PR	79 M, 6 PR
Load capacity 1 [kg]	437
Speed 1 [km/h].	130
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	8,93
ECE regulation number	ECE 54
Section width (mm)	138
Stat. radius (SLR) [mm]	239
Rolling circumference [mm].	1575

E-Ready	No
Assembly Item no. Rim	• 39600289
Load capacity of rim 1 [kg]	500
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	130
Maximum air pressure [bar].	3,40
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	14.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0

---

Valve angle [°]
-----------------

gerade
--------

---