

## WHEELS

Product group	Wheels
Item number	59696014
Valid wheel size	195 / 50 B 10
Brand	Kenda
Tread pattern	K399 Loadstar
Valid rim size	6.00 I x 10 H2
Rim connection	5/67/112
Bolt hole design	G12
Offset (mm)	-4
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	140



## Technical Informations

Assembly Item no. Tyres	• 19266067
LI / SI / PR	98 N, 8 PR
Load capacity 1 [kg]	750
Speed 1 [km/h].	140
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	12,03
ECE regulation number	ECE 54
Section width (mm)	185
Stat. radius (SLR) [mm]	210
Rolling circumference [mm].	1372

E-Ready	No
Assembly Item no. Rim	• 30855000
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	6,00
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade