

## WHEELS

|                                   |                |
|-----------------------------------|----------------|
| Product group                     | Wheels         |
| Item number                       | 59696015       |
| Valid wheel size                  | 195 / 50 B 10  |
| Brand                             | Kenda          |
| Tread pattern                     | K399 Loadstar  |
| Valid rim size                    | 6.00 I x 10 H2 |
| Rim connection                    | 5/94/140       |
| Bolt hole design                  | G1             |
| Offset (mm)                       | -4             |
| Rim colour                        | Silver         |
| Load capacity complete wheel [kg] | 750            |
| Speed complete wheel [km/h]       | 140            |



## Technical Informations

|                             |            |
|-----------------------------|------------|
| Assembly Item no. Tyres     | • 19266067 |
| LI / SI / PR                | 98 N, 8 PR |
| Load capacity 1 [kg]        | 750        |
| Speed 1 [km/h].             | 140        |
| Antistatic                  | No         |
| Tyre colour                 | Black      |
| Nettogewicht [kg] (gültig)  | 10,98      |
| ECE regulation number       | ECE 54     |
| Section width (mm)          | 185        |
| Stat. radius (SLR) [mm]     | 210        |
| Rolling circumference [mm]. | 1372       |

|                                |                |
|--------------------------------|----------------|
| E-Ready                        | No             |
| Assembly Item no. Rim          | • 30855002     |
| Load capacity of rim 1 [kg]    | 750            |
| Speed Rims 1 [km/h]            | 140            |
| Maximum speed [km/h].          | 140            |
| Maximum air pressure [bar].    | 6,00           |
| Type of drive                  | Towed axle     |
| Hump                           | H2             |
| Single / multi-part            | einteilig      |
| Rim material                   | steel          |
| RAL                            | RAL9006        |
| Cavity Sealed                  | No             |
| Ventilation holes              | No             |
| Verschweißung beidseitig       | No             |
| Rim centering                  | BC             |
| Number of bolt holes           | 5              |
| Bolt hole diameter [mm]        | 18.5           |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R14            |
| hub hole diameter [mm].        | 94             |
| Bolt hole circle diameter [mm] | 140            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 15.7           |
| Preassembled valve             | No             |
| Valve design                   | Metal valve    |
| Valve length [mm]              | 42.0           |
| Valve angle [°]                | gerade         |