

WHEELS

| | |
|-----------------------------------|------------------|
| Product group | Wheels |
| Item number | 59696021 |
| Valid wheel size | 155 R 13 |
| Brand | GT Radial |
| Tread pattern | KargoMax ST 4000 |
| Valid rim size | 4.5 J x 13 H2 |
| Rim connection | 4/57/100 |
| Bolt hole design | E16 |
| Offset (mm) | +30 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 500 |
| Speed complete wheel [km/h] | 140 |



Technical Informations

| | |
|----------------------------|----------------|
| Assembly Item no. Tyres | • 19866009 |
| LI / SI / PR | 84 N |
| Load capacity 1 [kg] | 500 |
| Speed 1 [km/h]. | 140 |
| M+S | M+S |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 12,14 |
| ECE regulation number | ECE 54 ECE 117 |
| Section width (mm) | 157 |
| Stat. radius (SLR) [mm] | 262 |

| | |
|---------------------------------|------------|
| Rolling circumference [mm]. | 1763 |
| Rolling resistance | C |
| Wet grip | C |
| Rolling noise [db]. | 70 |
| Rolling noise level | B |
| E-Ready | No |
| Assembly Item no. Rim | • 39600309 |
| Load capacity of rim 1 [kg] | 600 |
| Speed Rims 1 [km/h] | 140 |
| Maximum speed [km/h]. | 140 |
| Maximum air pressure [bar]. | 3,10 |
| Type of drive | Towed axle |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Disc thickness [mm] | 10 |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 4 |
| Bolt hole diameter [mm] | 15.5 |
| Countersinking | Cone |
| Countersinking of the cone [°]. | C60 |
| hub hole diameter [mm]. | 57 |
| Bolt hole circle diameter [mm] | 100 |

| | |
|--------------------------|----------------|
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.1 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |