

WHEELS

Product group	Wheels
Item number	59696022
Valid wheel size	155 R 13
Brand	GT Radial
Tread pattern	KargoMax ST 4000
Valid rim size	4.5 J x 13 H2
Rim connection	5/67/112
Bolt hole design	E12
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	500
Speed complete wheel [km/h]	140



Technical Informations

Assembly Item no. Tyres	• 19866009
LI / SI / PR	84 N
Load capacity 1 [kg]	500
Speed 1 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	12,04
ECE regulation number	ECE 54 ECE 117
Section width (mm)	157
Stat. radius (SLR) [mm]	262

Rolling circumference [mm].	1763
Rolling resistance	C
Wet grip	C
Rolling noise [db].	70
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30045101
Load capacity of rim 1 [kg]	625
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	3,10
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	4.25
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112

Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade