

## WHEELS

Product group	Wheels
Item number	59696023
Valid wheel size	175 R 13 C
Brand	GT Radial
Tread pattern	Maxmiler-X
Valid rim size	5 J x 13 H2
Rim connection	5/67/112
Bolt hole design	E16
Offset (mm)	+33
Rim colour	Silver
Load capacity complete wheel [kg]	725
Speed complete wheel [km/h]	140



Bohnenkamp  
■ ■ ● Moving Professionals

**GT** RADIAL

## Technical Informations

Assembly Item no. Tyres	• 19866011
LI / SI / PR	97 / 95 N, 8 PR
Load capacity 1 [kg]	730
Speed 1 [km/h].	140
Load capacity 3 [kg]	690
Speed 3 [km/h].	140
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	16,12
ECE regulation number	ECE 54 ECE 117
Section width (mm)	177

Stat. radius (SLR) [mm]	274
Rolling circumference [mm].	1861
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600301
Load capacity of rim 1 [kg]	725
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	4,50
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	15.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112

---

Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade