

WHEELS

Product group	Wheels
Item number	59696029
Valid wheel size	4.80 / 4.00 - 8
Brand	Kenda
Tread pattern	K358 Turf Rider
LI / SI / PR	54 A4 / 66 A4, 4 PR
TL/TT	TL
Hub design	End cap assembly
Type of bearing	Without bearing
Shaft diameter [mm].	46.9
Mounting length [mm]	82
Hub length [mm]	82
Rim colour	Silver
Load capacity complete wheel [kg]	212
Speed complete wheel [km/h]	6



Technical Informations

Assembly Item no. Tyres	19211169
LI / SI / PR	54 A4 / 66 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K358 Turf Rider
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar].	2,90
Section width (mm)	126
Rolling circumference [mm].	1242.00
Assembly Item no. Rim •	39600114
Valid rim size	2.50 A x 8
Load capacity of rim 1 [kg]	350
Speed Rims 1 [km/h]	6
Maximum speed [km/h].	6
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Verschweißung beidseitig	No
Offset hub	Yes
Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	12.0