

WHEELS

| | |
|-----------------------------------|------------------|
| Product group | Wheels |
| Item number | 59696059 |
| Valid wheel size | 15 x 6.00 - 6 |
| Brand | Deli |
| Tread pattern | S-317 |
| LI / SI / PR | 61 A6, 4 PR |
| TL/TT | TT |
| Hub design | End cap assembly |
| Type of bearing | Ball bearing |
| Shaft diameter [mm]. | 25 |
| Mounting length [mm] | 64 |
| Hub length [mm] | 74 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 257 |
| Speed complete wheel [km/h] | 30 |



Technical Informations

| | |
|-------------------------|-------------|
| Assembly Item no. Tyres | • 19110090 |
| LI / SI / PR | 61 A6, 4 PR |
| TL/TT | TT |
| Brand | Deli |
| Tread pattern | S-317 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |

| | |
|-----------------------------|----------------|
| Maximum air pressure [bar]. | 2,10 |
| Section width (mm) | 154 |
| Stat. radius (SLR) [mm] | 155 |
| Rolling circumference [mm]. | 1020 |
| Tread depth (mm) | 3,5 |
| Assembly Item no. Rim | • 39600299 |
| Valid rim size | 4.50 A x 6 H2 |
| Load capacity of rim 1 [kg] | 257 |
| Speed Rims 1 [km/h] | 30 |
| Maximum speed [km/h]. | 30 |
| Type of drive | Towed axle |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Number of drain holes | 3 |
| Verschweißung beidseitig | No |
| Offset hub | No |
| Additional socket required | No |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |
| Valve designation | TR 13 |